

CS10n

The CS10n is a two-way, full-range intelligent loudspeaker, intended for use in a wide variety of applications. Utilizing Adamson's proprietary network platform, the CS10n employs a redundant MILAN scheme with the ability to daisy-chain networked audio between multiple sources, an analog XLR input and output, as well as on-board DSP and amplification. All features of the loudspeaker are controlled and monitored through Adamson's proprietary CS software.

Acoustically, the CS10n contains 2x 10-inch Kevlar Neodymium transducers and a 4" compression driver. The critically optimized sound chamber produces a slightly curved wavefront with a nominal dispersion pattern of 80° x 10° (H x V). The narrower horizontal pattern allows for increased usability in reflective spaces as well as increased long-throw capability of a CS-Series package.

The cabinet construction uses marine grade birch plywood as well as aircraft grade steel and aluminum, and is equipped with a male and female XLR connector, 2x etherCON connections and an in and through powerCON TRUE1 connection.

Please refer to the CS10n User Manual for further information.



Technical Specifications

Frequency Range (+/- 3dB)	60 Hz - 18 kHz
Nominal Directivity (-6 dB) H x V	80° x 10°
Maximum Peak SPL **	141.3 dB
Components LF	2x ND10-LM 10" Kevlar Neodymium Driver
Components HF	Adamson NH4 4" Diaphragm / 1.5" Exit Compression Driver
Rigging	Slidelock Rigging System
Connections	Power: powerCON TRUE1 Network: 2x etherCON Analog: 2x XLR
Height Front (mm / in)	265 / 10.4
Height Back (mm / in)	178 / 7
Width (mm / in)	737 / 29
Depth (mm / in)	526 / 20.7
Weight (kg / lbs)	30.5 / 67
Amplification	2 channel Class-D, 2400W total output
Input Voltage	100 - 240v
Current Draw	0.45 A rms idle, 1.7 A rms long-term, 10 A max peak
Processing	Onboard / Proprietary

**12dB crest factor pink noise at 1m, free field, using specified processing and amplification

