



S119

The S119 Subwoofer is the companion subwoofer to the S10. The enclosure is loaded with a light weight, long excursion, 19" ND19 Kevlar Neodymium driver utilizing Adamson's Advanced Cone Architecture and a 5" voice coil for exceptional power handling. It is mounted in an ultra-efficient front-loaded enclosure, designed to reproduce clean, musical low frequency information.

The cabinet construction uses marine grade birch plywood as well as aircraft grade steel and aluminum, and is equipped with Speakon™ NL8 connectors. The integrated rigging system matches the rigging for the S10 and can be flown or stacked in the same array without the need for an adapter frame.

Specifications

Frequency Range (+/- 3dB)	30 Hz - 80 Hz
Maximum Peak SPL**	138 dB
Components LF	ND19 19" Kevlar Neodymium Driver
Nominal Impedance LF	8 Ω
Power Handling (AES / Peak) LF	1200 / 4800 W
Rigging	Integrated Rigging System
Connection	5x Speakon™ NL8: 2x Front (Pins 2 +/-), 2x Rear Parallel (Pins 1 +/-) and 1x Rear Output (Pin 2 to 1)
Height Front (mm / in)	543.5 / 21.4
Width (mm / in)	742 / 29.2
Depth (mm / in)	630 / 24.8
Weight (kg / lbs)	46 / 102
Supported Processing	Lake

**12 dB crest factor pink noise at 1m, half space, using specified processing and amplification

