





Part Number: 1813A

Audio Cable, #24-2c, BC, O/A Braid, CM

# **Product Description**

Audio Cable, CM-Rated, 1-24 AWG stranded high-conductivity bare copper pair with PVC insulation, +90% bare copper spiral shield, PVC jacket

# **Product Specifications**

#### **AG.Filter Attributes**

| Total Number of Conductors: | 2              |
|-----------------------------|----------------|
| lotal Number of Conductors. | 1 <sup>2</sup> |

# **Technical Specifications**

### **APAC Standard**

| MII Order #39 (China RoHS):      | Yes  |
|----------------------------------|------|
| init Gradi 1100 (Grinia 110110)1 | 1.00 |

#### **Applicable Patents**

| P | Patent: | http://www.belden.com/p |
|---|---------|-------------------------|
|   |         |                         |

### **Bend Radius**

| Min Bend Radius/Minor Axis: | 2.5 in |
|-----------------------------|--------|
| = 0.1.4 1.44.407.11.1101.   |        |

### **CCB-Sub-Part Number**

| Plenum (Y/N): | No |
|---------------|----|
|               |    |

#### **Contact Information**

| PHONE_NUM: | 1-800-Belden1 |
|------------|---------------|

### **EU Directive**

| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
|---------------------------------------|-------------------------------|
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-04-01                    |

# **North American Standard**

| CA Prop 65 (CJ for Wire & Cable): | Yes  |
|-----------------------------------|------|
| or the poor (or the distance).    | 1.60 |

### Use

| Max Recommended Pulling Tension: | 10 lbs |
|----------------------------------|--------|

#### Inductance:

#### Nominal Inductance

0.219 µH/ft

#### **Conductor DCR:**

| Nominal Conductor DCR No | ominal Outer Shield DCR |
|--------------------------|-------------------------|
| 22.8 Ohm/1000ft          | 11.6 Ohm/1000ft         |

#### **Color Chart 1:**

| Number | Color      |
|--------|------------|
| 1      | Blue & Red |

# Voltage:

# Non-UL Voltage Rating

100V RMS

### Capacitance:

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|---|---|
| 33 pF/ft                                | 61 pF/ft  |

### Insulation:

| Materi  | Nominal Diameter  |          |
|---------|-------------------|----------|
| PVC - F | plyvinyl Chloride | 0.059 in |

# Outerjacket 1:

| Material                 | Nominal Diameter |          |
|--------------------------|------------------|----------|
| PVC - Polyvinyl Chloride |                  | 0.236 in |

#### Conductor:

| AWG | Strar | nding Material                     | No. of Pairs |   |
|-----|-------|------------------------------------|--------------|---|
| 24  | 27x38 | High Conductivity BC - Bare Copper |              | 1 |

#### **Outershield 1:**

| Туре         | Material | Coverage [%]     |      |
|--------------|----------|------------------|------|
| Spiral Serve | В        | 3C - Bare Copper | 90 % |

#### **Product Variants**

| Part Number   | Color        | Put-Up Type | Length  |
|---------------|--------------|-------------|---------|
| 1813A         | BLACK, MATTE | Reel        | 1000 ft |
| 1813A         | MATTE BLACK  | Reel        | 305 m   |
| 1813A B591000 | BLACK, MATTE | Reel        | 1000 ft |
| 1813A         | BLACK, MATTE | Reel        | 328 ft  |
| 1813A         | MATTE BLACK  | Reel        | 100 m   |
| 1813A B59328  | BLACK, MATTE | Reel        | 328 ft  |
| 1813A         |              |             |         |

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor?s inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.