

**Part Number:** 8407

Microphone Cable, #16-4c, TC, O/A Braid, CM

## Product Description

16 AWG stranded (65x34) high-conductivity tinned copper conductors, EPDM rubber insulation, rayon braid, TC braid shield (85% coverage), cotton wrap, CPE jacket.

## Product Specifications

### AG.Filter Attributes

Total Number of Conductors:	4
-----------------------------	---

## Technical Specifications

### AG\_0401

UL Flammability:	VW-1
------------------	------

### APAC Standard

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

### Applicable Patents

Patent:	<a href="http://www.belden.com/p">http://www.belden.com/p</a>
---------	---

### Bend Radius

Min Bend Radius/Minor Axis:	4.25 in
-----------------------------	---------

### CCB-Sub-Part Number

Plenum (Y/N):	No
---------------	----

## Contact Information

PHONE_NUM:	1-800-Belden1
------------	---------------

## EU Directive

EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

## General Electrical Parameters

Other Electrical Characteristic 1:	2/c 13 AWG equivalent DCR when connected to a 3-pin XLR
------------------------------------	---

## North American Standard

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

## Unused Attributes

Notes:	Quad connection scheme: The black and red wires (or wires directly opposite one another) are connected together to form one conductor, and similarly the white and green wires (or remaining wires) are connected together to form the second conductor.
--------	--

## Use

Max Recommended Pulling Tension:	162 lbs
----------------------------------	---------

## Impedance:

Nominal Characteristic Impedance
44 Ohm

## Conductor DCR:

Nominal Conductor DCR	Nominal Outer Shield DCR
4 Ohm/1000ft	2.63 Ohm/1000ft

## Color Chart 1:

Number	Color
1	Black
2	White
3	Red
4	Green

**Delay:****Nominal Velocity of Propagation (VP) [%]**

52 %

**Voltage:****UL Voltage Rating**

600V RMS V

**Current:****Max. Recommended Current [A]**

5.6 Amps per conductor at 25°C

**Capacitance:****Nom. Capacitance Between Conductors in Quad****Nom. Capacitance Conductor to Conductor**

66 pF/ft

30 pF/ft

**Insulation:****Material****Nominal Diameter**

EPDM - Ethylene Propylene Diene Monomer Rubber

0.12 in

**Outerjacket 1:****Material****Nominal Diameter****Separator Material**

Neoprene

0.416 in

Rayon Braid

**Conductor:****AWG****Stranding****Material****Nominal Diameter****No. of Conductors**

16

65x34

High Conductivity TC - Tinned Copper

0.059 in

4

**Other Electrical Information:**

Other Electrical Characteristic 1

2/c 13 AWG equivalent DCR when connected to a 3-pin XLR

**Outershield 1:****Type****Material****Coverage [%]**

Braid

TC - Tinned Copper

85 %

Cotton Wrap in

## Product Variants

Part Number	Color	Put-Up Type	Length
8407	BLACK	Reel	100 ft
8407	BLACK	Reel	30 m
8407 010100	BLACK	Reel	100 ft
8407	BLACK	Reel	250 ft
8407	BLACK	Reel	76 m
8407 010250	BLACK	Reel	250 ft
8407	BLACK	Reel	76 m
8407			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.