



**Part Number:** 9151

Speaker Cable, #22-2c, BC, Unshielded, CM

## Product Description

22 AWG stranded (7x30) ETP high-conductivity copper conductors, PVC insulation, cabled: (1) tinned, (1) bare.

## Technical Specifications

### Construction and Dimensions

#### Conductor:

AWG	Stranding	Material	No. of Conductors
22	7x30	Tinned High-Conductivity ETP Copper	1
22	7x30	Bare High-Conductivity ETP Copper	1
<b>Total Number of Conductors:</b>			2

#### Insulation:

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.053 in

#### Outershield 1:

Material
Unshielded

#### Outerjacket 1:

Material	Nominal Diameter
Unjacketed	0.105 in

### Electrical Characteristics

#### Conductor DCR:

**Nominal Conductor DCR**

15 Ohm/1000ft

**Current:****Max. Recommended Current [A]**

2.9 Amps per conductor @ 25°C

**Inductance:****Nominal Inductance**

0.19 µH/ft

**Voltage:****UL Voltage Rating**

90V RMS V

**Use****Max Recommended Pulling Tension:**

17 lbs

**Safety****UL Flammability:**

VW-1

**Temperature Range****Non-UL Temp Rating:**

90°C °C

**Operating Temp Range:**

-35°C To +90°C °C

**Mechanical Characteristics****Min Bend Radius/Minor Axis:**

1.25 in

**Part Number****Plenum (Y/N):**

No

**Standards****CA Prop 65 (CJ for Wire & Cable):**

Yes

**MII Order #39 (China RoHS):**

Yes

**EU Directive Compliance:**

EU Directive 2003/11/EC (BFR)

**EU CE Mark:**

Yes

## Product Variants

Part Number	Color	Put-Up Type	Length
9151	WHITE	UnReel	1000 ft
9151	WHITE	UnReel	305 m
9151 009U1000	WHITE	UnReel	1000 ft
9151			

© 2017 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.