



Before using this unit, carefully read the sections entitled "USING THE UNIT SAFELY" and "IMPORTANT NOTES" (supplied on a separate sheet). After reading, keep the document(s) where it will be available for immediate reference.

Main Features

- The FZ-5 uses COSM technology to replicate three types of vintage fuzz boxes especially prized for their sound quality. These fuzz boxes incorporated germanium transistors in their circuitry, a key component to their sound. Germanium transistors are extremely rare today; the FZ-5 models these hard-to-find transistors at the component level to authentically reproduce the classic fuzz sounds of the 1960s and 1970s.
- The FZ-5's FUZZ knob features a BOOST range that allows you to achieve a deeper distortion than is possible with the original vintage models. Even single-coil pickups can be made to satisfyingly distort just like humbucking pickups.

COSM (Composite Object Sound Modeling)

Composite Object Sound Modeling—or "COSM" for short—is BOSS/Roland's innovative and powerful technology that's used to digitally recreate the sound of classic musical instruments and effects. COSM analyzes the many factors that make up the original sound—including its electrical and physical characteristics—and creates a digital model that accurately reproduces the original.

Panel Descriptions

DC IN jack

Accepts connection of an AC Adaptor (PSA series; sold separately). By using an AC Adaptor, you can play without being concerned about how much battery power you have left.

- * We recommend that you keep batteries installed in the unit even though you'll be powering it with the AC adaptor. That way, you'll be able to continue a performance even if the cord of the AC adaptor gets accidentally disconnected from the unit.
- * Use only the specified AC adaptor (PSA-series).
- * If the AC adaptor is connected while power is on, the power supply is drawn from the AC adaptor.



CHECK indicator

This indicator shows whether an effect is ON/OFF, and doubles as the Battery Check indicator. The indicator lights when an effect is ON.

- * If this indicator goes dim or no longer lights while an effect is ON, the battery is near exhaustion and should be replaced immediately.
- * The CHECK indicator shows whether the effect is on or off, and indicates the different functions. It does not indicate whether the power to the device is on or not.

LEVEL knob


This knob controls the volume of the fuzz effect.

MODE knob

This knob selects the fuzz box model. For details, refer to "MODE List."

OUTPUT jack

Connect this jack to the input of a guitar amp or another effects processor.



Pedal switch

This switch turns the effects ON/OFF.

Thumbscrew

When this screw is loosened, the pedal will open, allowing you to change the battery.

- * For instructions on changing the battery, refer to "Changing the Battery."

FUZZ knob

This knob controls the amount of fuzz effect applied. Turning the knob clockwise intensifies the distortion. Setting the knob at the center position produces the maximum distortion for the modeled fuzz box. Turning the knob into the BOOST range creates distortion even greater than the original model can produce.

INPUT jack


This jack accepts signals coming from a guitar or other musical instrument, or another effects unit.



- * The INPUT jack doubles as power switch. Power to the unit is turned on when you plug into the INPUT jack; the power is turned off when the cable is unplugged. When not using the effects unit, be sure to disconnect the plug from the INPUT jack.

Using the Mode Sticker

A mode sticker is included on this manual. This sticker provides a reminder about the various fuzz box models that can be selected with the MODE knob. To make use of the sticker, peel it off the backing paper and affix it as shown in the figure.



MODE List

F (FACE)	Models the Dallas-Arbitr FUZZ FACE. This unique round-shaped pedal was indispensable to the psychedelic fuzz sound of the late '60s. This modeled tone reproduces the fat sound of the Dallas-Arbitr units that used AC128 germanium transistors.
M (MST FUZZ)	Models the Maestro FZ-1A. It faithfully reproduces the sound of models equipped with 2N2614 germanium transistors. A characteristic of this fuzz sound is a prominent boost in the high-frequency range. If the FUZZ knob is set to the left of center, the sound might be interrupted or have insufficient volume. This is because the original unit is being faithfully modeled; it is not a malfunction.
O (OCTAVE FUZZ)	Models the Octavia fuzz. This model reproduces the original's characteristic of overlaying sound an octave higher as the sound decays. This distinctive sound can be obtained especially with single note in high pitch. Please try playing single note higher than 12th fret on 1st - 3rd string. Lowering the volume on the guitar or turning down the FUZZ knob makes it easier to obtain this effect.

Connections

- * Inserting a connecting plug into the INPUT jack turns on the power to the unit.
- * Raise the amp volume only after turning on the power to all connected devices.
- * The use of an AC adaptor is recommended as the unit's power consumption is relatively high.
- * If operating this unit on batteries, please use alkaline batteries.
- * To prevent malfunction and equipment failure, always turn down the volume, and turn off all the units before making any connections.
- * Some connection cables contain resistors. When connection cables with resistors are used, the sound level to be extremely low, or impossible to hear. For information on cable specifications, contact the manufacturer of the cable.
- * Once the connections have been completed, turn on power to your various devices in the order specified. By turning on devices in the wrong order, you risk causing malfunction and/or damage to speakers and other devices.

When powering up: Turn on the power to your guitar amp last.





When powering down: Turn off the power to your guitar amp first.

- * This unit is equipped with a protection circuit. A brief interval (a few seconds) after power up is required before the unit will operate normally.
- * Before turning the unit on/off, always be sure to turn the volume down. Even with the volume turned down, you might hear some sound when switching the unit on/off. However, this is normal and does not indicate a malfunction.
- * When operating on battery power only, the unit's indicator will become dim when battery power gets too low. Replace the battery as soon as possible.
- * If you handle batteries improperly, you risk explosion and fluid leakage. Make sure that you carefully observe all of the items

related to batteries that are listed in "USING THE UNIT SAFELY" and "IMPORTANT NOTES" (supplied on a separate sheet).

Operating the Unit


1. When you have made the necessary connections, set the knobs as shown in the illustration.
2. Depress the pedal switch to turn the effect on. (The CHECK indicator lights when the effect is on.)
3. Select the fuzz box model with the MODE knob.
4. Adjust the amount of distortion with the FUZZ knob. The original distortion range of the selected fuzz box model is reproduced when the FUZZ knob is set anywhere from fully counterclockwise to the center position. Turning the knob past the center position enables the BOOST range, which produces distortion that exceeds that available on the original model. The BOOST range provides plenty of distortion, even when using single-coil pickups.
5. Adjust the output volume with the LEVEL knob. Normally, you should adjust the LEVEL knob so there's no difference in the volume when switching the effect on and off.




МУЗЦЕНТР
МУЗЫКАЛЬНОЕ ОБОРУДОВАНИЕ
<https://muzcentre.ru>

Setting Samples


Psychedelic



Treble Fuzz




Octave Solo



Changing the Battery

1. Hold down the pedal and loosen the thumbscrew, then open the pedal upward. The pedal can be opened without detaching the thumbscrew completely.
2. Remove the old battery from the battery housing, and remove the snap cord connected to it.
3. Connect the snap cord to the new battery, and place the battery inside the battery housing. Be sure to carefully observe the battery's polarity (+ versus -).
4. Slip the coil spring onto the spring base on the back of the pedal, and then close the pedal. Carefully avoid getting the snap cord caught in the pedal, coil spring, and battery housing.
5. Finally, insert the thumbscrew into the guide bush hole and fasten it securely.



Main Specifications

BOSS FZ-5: Fuzz

Nominal Input Level	-20 dBu
Input Impedance	1 MΩ
Nominal Output Level	-20 dBu
Output Impedance	1 kΩ
Recommended Load Impedance	10 kΩ or greater
Power Supply	DC9V: Dry battery 6F22 (9V) type (carbon)/Dry battery 6LR61 (9V) type (alkaline), AC Adaptor (PSA-series: optional)
Current Draw	36mA (DC9V) * Expected battery life under continuous use: Carbon: 3 hours, Alkaline: 10 hours These figures will vary depending on the actual conditions of use.
Dimensions	73 (W) x 129 (D) x 59 (H) mm 2-7/8 (W) x 5-1/8 (D) x 2-3/8 (H) inches
Weight	440 g / 1 lb (including battery)
Accessories	Owner's manual, Mode sticker, leaflet ("USING THE UNIT SAFELY," "IMPORTANT NOTES," and "Information"), Dry battery 6LR61 (9V) type (alkaline)
Options	AC adaptor (PSA-series)

* 0 dBu = 0.775 Vrms

* This document explains the specifications of the product at the time that the document was issued. For the latest information, refer to the Roland website.