



### MAIN FEATURES

- Impressive sound pressure
- Real time monitoring via RNet protocol
- FIR Filters
- Front-fill use
- Wall-mountable
- Suitable for installation
- Ultra light-weight

### DESCRIPTION

The powerful and detailed sound of VIO X family into a small, ultra-performing cabinet: ideal as front-fill or under balcony in large VIO sound reinforcement systems and perfect for vertical or horizontal fixed installation.

VIO X205 fits any project as full-range PA, fixed installation, FOH monitoring, front-fill in large sound reinforcement systems, and more.

This solid wooden cabinet is reinforced with a polyurea finish and features M10 threaded nuts on top and bottom allowing installation with accessories WB-VIOX205 H (horizontal bracket) or WB-VIOX205 V (vertical bracket). The cabinet can be easily installed on pole thanks to SA-VIOX205 pole mount adaptor (35mm) allowing 2 tilt options.

### ACCESSORIES



WB-VIOX205V

Vertical bracket for VIO X205



WB-VIOX205H

Horizontal bracket for VIO X205



SA-VIOX205

Speaker stand adapter for VIO X205



FC-VIOX205

Functional cover for VIO X205

<b>Speaker Type</b>	2 Way Active Loudspeaker
<b>Frequency Response [-10dB]</b>	75 - 21.000 Hz
<b>Max SPL (1 m)</b>	126 dB
<b>Directivity X205-60</b>	60° x 60°
<b>Directivity X205-100</b>	100° x 100°
<b>HF</b>	1x 1", 1.4 v.c.
<b>LF</b>	2x 5", 1" v.c
<b>Amplifier</b>	400 W RMS Class-D Digipro® G3
<b>Power Supply</b>	Auto-range SMPS
<b>Limiter</b>	Peak, RMS, Thermal
<b>Processing</b>	FIR Linear Phase Filters
<b>Controller</b>	28/56 bit DSP
<b>AD/DA Converter</b>	24 bit/48 kHz
<b>Controls</b>	1x Rotary Encoder (8x EQ presets) 1x Input Attenuation Rotary Switch 1x On LED 1x Status LED 1x Signal LED 1x Limiter LED
<b>Signal Input</b>	1 x XLR balanced, 1 x RJ45 Link (RD-Net), 1x USB (Data Service)
<b>Signal Output</b>	1x XLR balanced, 1 x RJ45 Link (RD-Net)
<b>Housing</b>	Wooden Cabinet, Polyurea painting
<b>Wedge Angle</b>	5° Monitor use
<b>Rigging Points</b>	2x M10 Threaded Nuts (top and bottom)
<b>Width</b>	150 mm (5.9 in)
<b>Height</b>	485 mm (19 in)
<b>Depth</b>	240 mm (9.4 in)
<b>Weight</b>	7.8 kg (17.2 lbs)