

TWINAXIAL SPEAKER CABLES



ANALOG

OFC

HIGHFLEX

GBR 240 / GBR 440

CONSTRUCTION DATA

Core Section	4 mm ²
Stranded Copper Conductor	127 x 0,20mm Ø Stranded copper (12 AWG)
Conductor Insulation	4 ± 0,05 mm Ø PVC
Conductor Color Code	Blue / Red / White / Green / Yellow
	GBR 240 GBR 440
Core Numbers x Section:	2 x 4,0 mm ² 4 x 4,0 mm ²
Outer Sheath	s-PVC Matt Black s-PVC Matt Black
Outer Diameter	10,2 ± 0,10 mm Ø 12,2 ± 0,10 mm Ø
Weight	16,7 kg/100m 27,1 kg/100m

ELECTRICAL DATA

Conductor Resistance	< 4,5 Ω / km
Insulation Resistance	> 2000 MΩ x km
Capacitance	180 pF / m
Inductance	0.5 μH / m
Test voltage	2 kV
Max. Operating Voltage	300 V

MECHANICAL DATA

Mobile installation	- 5° C to + 70° C
Fixed installation	-25° C to +70° C

APPLICATION

Proflex range of two core speaker cables suitable for high-end hi-fi equipment, rehearsal space, recording studio, and live arena applications.

Stranded Pure Copper (OFC) Conductors, PVC Insulation, Matt Black PVC Sheath

ISO9001
CERTIFIED



MOBIL
STUDIO
INSTALLATION
STAGE
GABRIEL