

MUSUKANAHOE OFOPYNOBAHUE

https://muzcentre.ru

## Users' Manual

The JTS UA-900 is a full range UHF antenna splitter that routs antenna signals from a pair of antenna to several receivers in a multi-channel statem.

The UA-900 also amplifies the RF signals to compensate the loss incured from splitting signal power.

Built-in DC distributtion provides four DC 12V power supply for receivers.

A single UA-900 can support up to four wireless receivers. Multiple UA-900 can be cascaded for more wireless receivers.

## Specification:

Frequency Range: 470-870 MHz RF Output Level(Gain):-0.5 to 3dB Output Connection Isolation:>=25 dB

Third Order Intercept Point:24 dBm

Impedance:50 Ohm

Input AC Voltage: 90-260 V switching power

Output DC Voltage: 12-18 V, 4 Connectors Antenna Booster DC Voltage: 12-18 V

Dimension: 250\*480\*45 mm (standard 19" and 1 U case)

Net Weight: 2.15 kg

#### System Components

DC cable for receiver connection X 4 pieces

Antenna cables for receiver connection and front antennas X 10 pieces

AC cord X 1 piece

Front-mount antenna hardware

### Connections

1.Single UA-900; See illustration No.1

2.Multiple UA-900: See illustration No.2

## Feature

- Powre On/Off switch
- ② AC INPUT
- 3 DC OUTPUT
- ANT. A IN
  ANT. B IN
- \_\_\_\_\_
- 6 ANT. A OUTPUT
- ② ANT. B OUTPUT
- ® ANT






CE FCC



## Connection for one UA-900



# Connection for multiple UA-900

