

# Speaker Cable SC-AQUA MARINEX EL 440; 4 x 4,00 mm<sup>2</sup>; PUR-SR with ARAMID reinforcement and special protective coating Ø 13,00 mm; black

Art. No.: 490-0231-440AQ

**ANALOG** **AQUA** **HALOGEN-FREE** **OFC** **PUR**

## General Data


Article number :	490-0231-440AQ
Name :	SC-AQUA MARINEX EL 440
EAN :	4049371441933
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	PUR
Properties :	Digital 75 Ω
Properties :	Underwater / submerged
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Colour :	black
BPVo-Euroclass :	Fca

## Technical Data

Signal transmission :	
Signal transmission :	
Jacket material :	PUR-SR with ARAMID reinforcement and special protective coating
Jacket Ø [mm] :	13,00
Inner conductor (audio) :	4
Inner conductor (audio) [mm <sup>2</sup> ] :	4,00
AWG (audio) :	11
Copper strands (audio) :	126
Copper strand Ø (audio) [mm] :	0,20
Conductor insulation material :	PE
Conductor insulation Ø [mm] :	3,80
Weight per 1 m [g] :	285
UV-resistant :	yes
Fire load per m [kWh] :	0,95
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-40
Temperature max. [°C] :	80
Width [mm] :	13
Height [mm] :	13

## Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	90
Insulation resist. per 1 km [GΩ] :	0,5



Insulation resist. per 1 km (audio) [GΩ] :	0,5
Conductor resistance per 1 km [Ω] :	4,95
Test voltage [V] :	2000
Nominal voltage (power) [V] :	500