

Speaker Cable SC-AQUA MARINEX SPEAKER 225; 2 x 2,50 mm²; PUR-SR Ø 8,20 mm; black

Art. No.: 425-0241AQ



General Data

Article number :	425-0241AQ
Name :	SC-AQUA MARINEX SPEAKER 225
EAN :	4049371194440
Properties :	Analog
Properties :	Halogen-free / LSZH
Properties :	PUR
Properties :	Digital 75 Ω
Properties :	Underwater / submerged
Application area :	Stage / live
Application area :	Mobile outdoor / indoor
Application area :	Installation
Application area :	ELA 100 V
Application :	Speaker Cable
Colour :	black
BPVo-Euroclass :	Fca

Technical Data

Jacket material :	PUR-SR
Jacket Ø [mm] :	8,20
Number of Channels (audio) :	1
Inner conductor (audio) :	2
Inner conductor (audio) [mm ²] :	2,50
AWG (audio) :	13
Shielding :	CU braiding + special protective banding
Shielding factor [%] :	85
Copper strands (audio) :	142
Copper strand Ø (audio) [mm] :	0,15
Conductor insulation material :	PO
Conductor insulation Ø [mm] :	2,60
Weight per 1 m [g] :	117
UV-resistant :	yes
Fire load per m [kWh] :	0,28
Style variant :	round
Packing :	bulk stock
Temperature min. [°C] :	-40
Temperature max. [°C] :	80
Width [mm] :	8,2
Height [mm] :	8,2

Electrical Data

Capac. cond./cond. per 1 m (audio) [pF] :	90
Insulation resist. per 1 km [GΩ] :	1

Insulation resist. per 1 km (audio) [GΩ] :	1
Conductor resistance per 1 km [Ω] :	8,21
Shield. resistance per 1 km [Ω] :	16,2